




- **Capacity:** 1,000lb (453kg) to 3,500lb (1587kg) maximum hoist capacity, capable of the full rated capacity in *any* position without restriction.
- **Stowed dimension:** From 79in / 2m to 144in /3.65m measured from the center of rotation to the end of the boom.
- **Hydraulic telescoping boom:** Lengths available from 121in (3m) to 240in / 6.10m.
- **Hydraulic Linear Winch system:** Standard with integrated lift overload protection; a totally non-fouling, silent operating winch design.
- **Constant Payout:** Hydraulic linear winch travels with the telescoping boom extension enabling constant cable payout length for superior control and ease of operation.
- **Hydraulic boom luffing:** Capable of the full rated capacity at any boom angle.
- **Hydraulic cylinders:** With integrated safety valves for unsurpassed dependable safe operation.
- **Hydraulic Power Unit:** Available based on davit system requirements.
- **Hydraulic power rotation/slewing** For enhanced control and ease of operation.
- **Remote Control:** Hand held push button/rocker switch available in tethered or wireless proportional.
- **Mounting:** Aluminum standpipe, thru deck mount or pedestal base deck mount, bolt or weld down style .
- **Paint:** The davit is finished to Nautical Structures highest level of quality with urethane paint products.
- **Testing:** System assembled and tested prior to shipment.
- **1-YEAR WARRANTY:** Including materials and workmanship, electrical, hydraulic and labor, see warranty for details.



	CAPACITY		DIMENSION				MODEL	CERTIFICATION	
			A:(Min)		B:(Max)				
	lb	kg	in	m	in	m			
T7	1000	454	79	2.01	121	3.07	NS10-EX-79-121		
			91	2.31	145	3.68	NS10-EX-91-145		
	1200	545	79	2.01	121	3.07	NS12-EX-79-121		
			91	2.31	145	3.68	NS12-EX-91-145		
T10	1500	680	97	2.46	145	3.68	NS15-EX-97-145		
			109	2.77	169	4.29	NS15-EX-109-169		
	1700	771	97	2.46	145	3.68	NS17-EX-97-145		
			109	2.77	169	4.29	NS17-EX-109-169		
	2000	907	97	2.46	145	3.68	NS20-EX-97-145		
			109	2.77	169	4.29	NS20-EX-109-169		
	2200	998	97	2.46	145	3.68	NS22-EX-97-145		
			109	2.77	169	4.29	NS22-EX-109-169		
	2500	1134	97	2.46	145	3.68	NS25-EX-97-145		
			109	2.77	169	4.29	NS25-EX-109-169		
	T14	2000	907	120	3.05	192	4.88	NS20-EX-120-192	MCA
				135	3.43	216	5.48	NS20-EX-135-216	MCA
144				3.65	240	6.09	NS20-EX-144-240	MCA	
2200		998	120	3.05	192	5.49	NS22-EX-120-192	MCA	
			135	3.43	216	5.48	NS22-EX-135-216	MCA	
			144	3.65	240	6.09	NS22-EX-144-240	MCA	
2500		1134	120	3.05	192	6.1	NS25-EX-120-192	MCA	
			135	3.43	216	5.48	NS25-EX-135-216	MCA	
			144	3.65	240	6.09	NS25-EX-144-240	MCA	
3000		1361	120	3.05	192	4.88	NS30-EX-120-192	MCA	
			135	3.43	216	5.48	NS30-EX-135-216	MCA	
3500		1588	120	3.05	192	4.88	NS35-EX-120-192	MCA	
3500	1588	135	3.43	216	5.48	NS35-EX-135-216	MCA		

7301 114th Avenue North • Largo, Florida 33773

Phone: (727) 541-6664 • Facsimile: (727) 541-6353 • North America Toll Free: (888) 541-6664

Email: sales@nautical-structures.com • www.nautical-structures.com